

CONGRATULATIONS!!!

You have just purchased the most advanced live bait system on the market today! Your new **SUPER BAIT TANK II** is a hand-crafted piece of equipment and should be treated with the care of any other equipment. The following guidelines will assure you maximum efficiency.

1. Remove the top from tank.
2. Remove filter box and scale catcher from filter compartment.
3. The filter material used is either activated carbon or a fiber material called poly-fil, which can be purchased at any Wal-Mart in the fabric department.
4. Inside the filter box is a 1" pipe called the standpipe. Fill filter box with media to within 2" of the top of the standpipe. If using activated carbon, this must be rinsed thoroughly to remove carbon dust.
5. No media goes in the scale catcher. You use it "as is".
6. After filling the filter box with media, replace scale catcher and plug filter box back into the 90 degree elbow at the bottom of the filter compartment.
7. You will also need to use a product to remove ammonia. There are some liquid products that will do this. I prefer to use a product called Zeolite. This can be ordered from Livewell Systems. This material is placed in some type of mesh bag and rinsed to remove dust. Place this bag on the floor of the filter compartment filter box.
8. Start to fill the tank with water, adding necessary chemicals.
 - a) Rock Salt (ice cream salt) - 1/2 lb. to 20 gals, 1 lb. to 30 gals., 1-1/2 lbs. to 40 gals., 2 lbs. to 50 gals.
 - b) One tablespoon Bait Saver or 4 oz. Shad Saver to 30 gals. water.
 - c) Cool water with ice in the summer months to a temperature of around 65 degrees. This temperature may rise into the low 70's.
 - d) Mix all chemicals thoroughly and continue to fill tank.

IMPORTANT! IMPORTANT!

9. It is very important that you obtain the proper water level. To do this, fill tank until water starts to overflow the standpipe with the scale catcher in place. As soon as the pump is covered with water, connect pump to battery. With the pump running, continue to fill until the filter compartment is half full of water. **THE WATER LEVEL IN FILTER COMPARTMENT SHOULD NEVER BE MORE THAN HALF FULL WITH THE PUMP RUNNING.**

ATTENTION! ATTENTION!

Your new Super Bait Tank II is now equipped with the Keep-Alive Oxygen Infuser. This system brings in outside air and mixes it at the pump to produce millions of dust size bubbles. The following guidelines will assure that the system is operating properly.

- a) Turn the Air Control Valve clockwise until it is fully closed.
 - b) Connect pump to battery. Make sure that the **BROWN** lead goes to the positive (+) side of the battery.
 - c) Slowly turn the Air Control Valve counter clockwise until you see a steady stream of bubbles.
10. You are now ready to add bait. The following numbers are basic guidelines. They will vary depending on the time of year and size of bait:
- | | |
|---------------------------|---------------------------|
| a) 20 gal. - 2 to 3 dozen | b) 30 gal. - 4 to 5 dozen |
| c) 40 gal. - 6 to 7 dozen | d) 50 gal. - 7 to 8 dozen |
11. The scale catcher should be checked periodically and emptied if necessary. It is important to remove the scale catcher when holding bait overnight and you are away from the tank.
12. If the water should start to foam, a de-foaming agent should be added.
13. If you use activated carbon, please call for cleaning instructions. To clean the Zeolite, just rinse with fresh water and allow to dry. After 3-4 uses, it should be soaked in a strong saltwater solution. Mix 1 lb. salt in 2 gals. water and soak for 24 hours. Rinse with fresh water.

We at Livewell Systems thank you for your purchase and support. If you have any questions, please call:

Ron Vest @ (864) 295-4206

Livewell Systems, Inc.
614 Old Pendleton Road
Easley, SC 29642